



400W PC Power Supply

Features:



80 PLUS BRONZE Efficiency at 230V



85% minimum efficiency at 50% load



12cm Fan

Whisper quiet 12cm fan brings more airflow volume with less noise than convention.



Honey Comb Structure with the Best Ventilation Optimum structure for the best ventilation and maximize air flow to solve potential

thermal and noise problem. Reduce the air resistance to minimum.

PC Connecto

PCI-Express Power Connectors Provide dedicated +12V for high end dual graphic cards.



Dual + 12V Output Rails Ensure safe and stable system operation under heavy operation.



Output 24 Pin Cable with Nylon Sleeve The cable sleeve avoids cable clutter, allows neat and easy installation for an improved airflow.



Patented Easy Swap Connector

Quick and Easy installation.



ErP Compliance

Its standby and off mode wouldn't exceed 0.5W consumption to save energy and maintain sustainable environment.









400W PC Power Supply

Specification:

| Model no. | | PA0088 | PA0089 | PA0090 |
|---------------------------|---------------|--------------------|--------------------|--------------------|
| Input | Voltage | 230V | 230V | 100-240V |
| | Current | 6.3A | 6.3A | 10A |
| | Total Watts | 400W | 700W | 750W |
| Output | +5V | 20A | 22A | 22A |
| | +3.3V | 20A | 22A | 22A |
| | +12V1 | 16A | 52.5A | 62.5A |
| | +12V2 | 16A | - | - |
| | -12V | 0.3A | 0.3A | 0.3A |
| | +5Vsb | 2.5A | 2.5A | 3.0A |
| | +5V+3.3V | 103W | 130W | 120W |
| | +12V Combined | 360W | 630W | 750W |
| PCI-Express Connectors | 20+4pin | 1 | - | - |
| | 24pin | - | 1 | 1 |
| | CPU 4pin | 1 | 0 | 0 |
| | CPU 4+4pin | 0 | 1 | 1 |
| | CPU 8pin | 0 | 0 | 0 |
| | PCI-E 6+2pin | 0 | 4 | 4 |
| | PCI-E 6pin | 1 | 0 | 0 |
| | SATA | 3 | 6 | 8 |
| | HDD | 3 | 3 | 4 |
| | FDD | 1 | 1 | 1 |
| Dimension (WxDxH) | | 150x140x86mm | 150x160x86mm | 150x160x86mm |
| Weight | | 1.55kg | 1.75kg | 1.85kg |
| Fan Bearing | | Sleeve bearing fan | Sleeve bearing fan | Sleeve bearing fan |
| PFC | | Active PFC | Active PFC | Active PFC |
| Fan Size (cm) | | 12cm | 13.5cm | 13.5cm |
| Operating Temperature | | 0°C ~ 40°C | 0°C ~ 40°C | 0°C ~ 40°C |
| Storage Temperature | | -40°C ~ 70°C | -40°C ~ 70°C | -40°C ~ 70°C |



RoHS compliant CE

* The specifications and pictures are subject to change without notice. *All trade names referenced are the registered namework of their respective owners.






400W PC Power Supply

| Modular Cable | - | - | Semi-modular |
|------------------------|-------------------|----------------------|--------------------|
| Easy Swap Connector | V | V | v |
| Japanse Capacitors | - | - | Main |
| Solid-state Capacitors | - | - | v |
| Cable Sleeve | Main cable | Fully | Fully |
| Flat Cable | - | - | v |
| +12V Rail | 2 Rails | 1 Rail | 1 Rail |
| Protection | UVP/OVP/OPP/ | UVP/OVP/OPP/ | UVP/OVP/OPP/ |
| | SCP | SCP | SCP/OCP/OTP |
| Safety | CE, TUV, CB | CE, TUV, CB | CE, TUV, CB |
| 80 Plus | Bronze | Bronze | Gold certificate |
| Efficiency | 85% efficiency (a | t 85% efficiency (at | 90% efficiency (at |
| | 50% load) | 50% load) | 50% load) |
| ErP Complaint | ErP | ErP | ErP |

Connectors:








RoHS compliant



400W PC Power Supply





RoHS compliant

CE


PA0088 4 052792 031461 Made in China

* The specifications and pictures are subject to change without notice. *All trade names referenced are the registered namework of their respective owners.





400W PC Power Supply



Package Contents:

- 400W PC Power Supply x 1
- User Manual x 1

Packaging Information:

- Packing Dimension: 235 x 178 x 100mm
- Packing Weight: 1.9kg
- Carton Dimension: 525 x 480 x 200mm
- Carton Q'ty: 10pcs
- Carton Weight: 20kg



RoHS compliant

CE





Made in China