

LogiLink

PCI Express Card 2 Serial Ports + 1 Parallel Port

Art. No.: PC0033

LogiLink PCI Express Card extends your PC by two serial and one parallel ports connect RS232 as well as DSUB25 compatible devices. The internal and external connections are standardized and work in any PC.

Features:

- » 2x RS232 9-pin external and 1x D-SUB 25-pin external
- » Compliant with PCI Express 2.0
- » Compliant with PCI Power Management 1.2
- » With 256-byte Transmit/Receive FIFO, Single-lane (x1) PCI-Express
- » Supports hardware and software flow control
- » Automatic IRQ address
- » Supports Slow IrDA mode (up to 115200 bps) on all serial ports and parallel ports
- » Supports SPP, Nibble, Byte, ECP modes
- » Supports remote wakeup and power management features
- » Compatible with industrial standard 16C450/16C550 UART
- » Supports Windows, Linux and DOS




Serial device with D-Sub 9P

Download the driver online if required: http://downloads.2direct.de/treiber/PC0033.zip











Specifications:

Chipset	ASIX AX99100
Output Ports	2 x DB9 female (serial) 1 x DB25 female (parallel)
Interface (Bus) Type	1 x PCI Express
PCI-Express Revision	2.0
Max. Data Transfer Rate	Serial: 115200 bps Parallel: 1520000 bps
Transmit-Receive FIFO	256 byte
RS232 Flow Control	Hardware/Software flow control
Physical PCI Express link	Single link (x1)
Power Management	1.2
Remote Wakeup	Yes
IEEE1284	Yes
Automatic IRQ Address	Yes
Bidirectional	Yes
Parallel Modes	SPP/Nibble/Byte/ECP
Compability	Windows/Linux/Dos
Operating Temperature	0–70 °C
Operating Humidity	0–90% RH (non-condensing)
Dimensions	DB9: 7.2 x 11.97 x 2.18 cm DB25: 7.94 x 11.97 x 2.18 cm
Weight	76.4 g

Package Contents:

- » 1 x PCI Express Card, 2x Serial & 1x Parallel
- » 3 x Low Profile Brackets
- » 1 x User Manual

Package Information:

- » Packing Dimension: 175 x 140 x 37 mm
- » Packing Weight: 0.15 kg
- » Carton Dimension: 490 x 380 x 345 mm
- » Carton Q'ty: 50 pcs
- » Carton Weight: 8.6 kg



