

# LogiLink

USB 3.2 Gen 1 to VGA Adapter with PD

Art. No.: UA0259

The USB-C<sup>™</sup> to VGA Charging Adapter lets you connect your MacBook or Chromebook from a USB-C<sup>™</sup> port to a VGA display, while also connecting a standard USB-C<sup>™</sup> charging cable.

This Adapter allows you to mirror your MacBook display to your VGA-enabled TV or monitor up to 1080p HD; it also outputs video content like movies and captured video.

Simply connect the adapter to the USB-C<sup>™</sup> port on your MacBook or Chromebook and then to your TV or projector via a VGA cable (sold separately).

You can also connect a charging cable to the USB-C<sup>™</sup> port to charge your MacBook or Chromebook.

#### **Features:**

- » Support USB-C<sup>TM</sup> input and VGA output
- » Supports DisplayPort 1.2 Alt-mode

» Easy to use and carry

- » Supports VGA resolution up to 1920 x 1200 @60Hz
- » Supports both video and audio output
- » USB-C<sup>™</sup> female port supports USB Power Delivery Profile 4 up to 60W (20V/3A)

» Supports simultaneous charging to your MacBook or Google Chromebook, or any other USB-C<sup>™</sup> supported devices

- VGA cable (Not included) • (\*\*\*\*\*) • Macbook ( ( Device Charging Chromebook **Monitor/TV**





RoHS

\*Specifications are subject to change without prior notice. \*USB Type-C™ and USB-C™ are trademarks of USB Implementers Forum. \*All trade names referenced are the registered trademark of their respective owners.





# LogiLink

USB 3.2 Gen 1 to VGA Adapter with PD

Art. No.: UA0259

#### **Specification:**

Input	1x USB-C <sup>™</sup> Male 1x USB-C <sup>™</sup> Female for charging
Output	1x VGA Female
VGA Resolutions	Up to 1920 x 1200 @60Hz
VGA per Lane Data Rates	5.4 Gbps (HBR2), 2.7 Gbps (HBR) and 1.62 Gbps (RBR)
USB-C™ Standard	USB 3.1 Gen1 (Thunderbolt™ 3 compatible)
Operating Temperature	0°C - 45°C
Operating Humidity	10 - 85% RH (no condensation)
Storage Temperature	-10°C - 70°C
Storage Humidity	5 - 90% RH (no condensation)
USB-C <sup>™</sup> Female Charging Port	USB PD Profile 4 Source up to 60W (20V/3A)
Product Dimension	59.1x40.2x14.4 mm
Product Weight	30 g
Cable Length	14 cm

## **Compatible Devices:**

Apple	2015 MacBook 2016 MacBook 2016 MacBook Pro
Dell	XPS 13
Google	Chromebook Pixel
HP	Elite x2 1012 G1 Pro Tablet 608
Samsung	900X5L-K01



## Package Contents:

- » 1x USB 3.2 Gen 1 to VGA Adapter with PD
- » 1x User Manual

#### **Package Informations:**

- » Packing Dimension: 202x139x25 mm
- » Packing Weight: 0.085 kg
- » Carton Dimension: 520x366x 85 mm
- » Carton Q'ty: 40 pcs
- » Carton Weight: 4.2 kg



Proper use of the PD function can only be guaranteed in combination with certified USB cables with E-Mark chipset.

\*Specifications are subject to change without prior notice. \*USB Type-C<sup>™</sup> and USB-C<sup>™</sup> are trademarks of USB Implementers Forum. \*All trade names referenced are the registered trademark of their respective owners.



